

max. 102 m³/h

DC Axial Fans

Series 3400 N 92 x 92 x 25 mm



Highlights:

- Ball bearings and sleeve bearings available.
- Some models suitable for use at high ambient temperatures to 85 °C.

General characteristics:

- Material: fiberglass-reinforced plastic. Impeller PA, housing PBT.
- Fully integrated electronic commutation.
- Protected against reverse polarity and blocking.
- Electrical connection via single leads AWG 24, TR 64. Stripped and tinned ends.
- Blowing over struts. Rotational direction CCW looking at rotor.
- Mass: 100 g.

Nominal Data	Air Flow		Nominal Voltage	Voltage Range	Noise	Sound Power	Sinter-Sleeve Bearings Ball Bearings	Power Input	Nominal Speed	Temperature Range	Service Life L ₁₀ (40 °C) ebm-papst Standard	Service Life L ₁₀ (T _{max}) ebm-papst Standard	Life expectancy L ₁₀ Δ (40 °C) see page 13	Curve	Specials
	m ³ /h	CFM													
3412 NGL	61	35.9	12	8...15	23	4.0	□	1.1	1 950	-20...+80	80 000 / 30 000	160 000	160 000	1	
3412 NLE	61	35.9	12	8...15	23	4.0	■	0.8	1 950	-20...+85	80 000 / 27 500	160 000	160 000	1	
3412 NGME	72	42.4	12	8...15	28	4.3	□	1.6	2 300	-20...+75	75 000 / 32 500	150 000	150 000	2	
3412 NME	72	42.4	12	8...15	28	4.3	■	1.1	2 300	-20...+75	75 000 / 32 500	150 000	150 000	2	/2
3412 NG	84	49.4	12	8...15	32	4.7	□	2.2	2 700	-20...+70	70 000 / 35 000	140 000	140 000	3	/2
3412 N	84	49.4	12	8...15	32	4.7	■	2.2	2 700	-20...+70	70 000 / 35 000	140 000	140 000	3	/2
3412 NGH	94	55.3	12	8...15	36	5.0	□	2.5	3 000	-20...+70	70 000 / 35 000	140 000	140 000	4	
3412 NH	94	55.3	12	8...15	36	5.0	■	2.5	3 000	-20...+70	70 000 / 35 000	140 000	140 000	4	/2;/39
3412 NGHH	102	60.0	12	8...13.2	39	5.1	□	3.2	3 250	-20...+60	70 000 / 45 000	140 000	140 000	5	/2
3412 NHH	102	60.0	12	8...13.2	39	5.1	■	2.9	3 250	-20...+60	70 000 / 45 000	140 000	140 000	5	/2
3412 NHH-379	102	60.0	12	8...15	39	5.1	■	2.7	3 250	-20...+70	70 000 / 35 000	140 000	140 000	5	
3414 NGL	61	35.9	24	18...28	23	4.0	□	1.4	1 950	-20...+70	80 000 / 40 000	160 000	160 000	1	
3414 NL	61	35.9	24	18...28	23	4.0	■	1.4	1 950	-20...+70	80 000 / 40 000	160 000	160 000	1	
3414 NGM	72	42.4	24	18...28	28	4.3	□	1.8	2 300	-20...+70	75 000 / 37 500	150 000	150 000	2	
3414 NM	72	42.4	24	18...28	28	4.3	■	1.8	2 300	-20...+70	75 000 / 37 500	150 000	150 000	2	
3414 NG	84	49.4	24	18...28	32	4.7	□	2.3	2 700	-20...+70	70 000 / 35 000	140 000	140 000	3	
3414 N	84	49.4	24	18...28	32	4.7	■	2.3	2 700	-20...+70	70 000 / 35 000	140 000	140 000	3	/2
3414 NGH	94	55.3	24	18...26	36	5.0	□	3.0	3 000	-20...+70	70 000 / 35 000	140 000	140 000	4	/2
3414 NH	94	55.3	24	18...26	36	5.0	■	3.0	3 000	-20...+70	70 000 / 35 000	140 000	140 000	4	
3414 NGHH	102	60.0	24	18...26	39	5.1	□	3.2	3 250	-20...+70	70 000 / 35 000	140 000	140 000	5	
3414 NGH-389	102	60.0	24	18...28	39	5.1	□	3.2	3 250	-20...+70	70 000 / 35 000	140 000	140 000	5	
3414 NHH	102	60.0	24	18...26	39	5.1	■	3.2	3 250	-20...+70	70 000 / 35 000	140 000	140 000	5	/39
3414 NHH-386	102	60.0	24	18...28	39	5.1	■	3.2	3 250	-20...+70	70 000 / 35 000	140 000	140 000	5	
3418 N	84	49.4	48	36...56	32	4.7	■	2.4	2 700	-20...+70	70 000 / 35 000	140 000	140 000	3	

Other 48 V DC Models on request.

